


Lot 1 - Item no. 1: A4 Laserjet Printer

Restricted to HP Brand only

Item Name	Parameters	Required Specifications
A4 Laserjet Printer	Print Technology	Laser
	Print Size	Up to A4
	Print Speed (Black)	Up to 40/38 ppm
	ADF	Yes
	Network Printing	Yes (through RJ45)
	Duty Cycle	Up to 80,000 pages per month
	Resolution	Up to 1200 x 1200 dpi
	Processor	1200 MHz
	Memory (Standard)	128 MB
	Paper Handling Capacity (Standard)	150 sheets
	Duplex Printing: Automatic (Standard)	Yes
	Accessories	Drivers and Power and Data cable
	Connectivity (Standard)	1 Hi-Speed USB 2.0, 1 Host USB, 1 Ethernet 10/100/1000 Gigabit network
Operating System Support	MS Windows XP, Windows 7, Windows 8	
Warranty	1 year	




Technical Specifications

Lot 1 - Item No. 2: A4 Color Printer

Restricted to HP Brand only


Item Name	Parameters	Required Specifications
A4 Color Printer	Print Technology	Laser
	Print Size	Up to A4
	Print Speed (colour print)	Up to 18 ppm colour print
	ADF	Yes
	Network Printing	Yes (through RJ45)
	Duty Cycle	Up to 30,000 pages per month
	Resolution	Up to 600 x 600 dpi
	Processor	800 MHz
	Memory (Standard)	128 MB
	Paper Handling Capacity (Standard)	150 sheets
	Duplex Printing: Automatic (Standard)	Yes
	Accessories	Drivers and Power and Data cable
	Connectivity	Standard connectivity: Hi-Speed USB 2.0 port; built-in Fast Ethernet 10/100Base-TX network port Mobile print capability: HP ePrint,
Operating System Support	Windows® 10, 8.1, 8, 7; Windows Vista®; Windows® XP SP3 or higher; Apple® OS X: Sierra (v10.12), El Capitan (v10.11), Yosemite (v10.10), Mavericks (10.9), Mountain Lion (10.8), Lion (10.7); Linux; Mobile Operating Systems: iOS, Android, Windows 8 RT;	
Warranty	1 year	




Lot1 - Item no. 3: A4 Laserjet Multifunction Printer

Note: Restricted to HP Brand only

Item Name	Parameters	Required Specifications
A4 Laserjet Multifunction Printer	Functions	Print, Copy, Scan, Fax, Walk-up USB
	Print speed (black, normal quality, A4)	Up to 38 ppm
	Network Printing	Yes
	Duty Cycle	Up to 50,000 pages
	Resolution	Up to 1200 x 1200 dpi
	Processor speed	600 MHz
	Standard memory	256 MB
	Paper Handling Capacity (Standard)	250 sheets
	Duplex Printing (Standard)	Yes
	Copy speed (black, draft quality, A4)	Up to 35 cpm
	Maximum number of copies	Up to 99 copies
	Copy resolution (black graphics)	Up to 600 x 600 dpi
	Copier resize	25 to 400%
	Scan type	Flatbed, ADF
	Enhanced scanning resolution	Up to 19200 dpi
	Optical scanning resolution	Up to 1200 dpi (Monochrome), 600 (Colour scanning)
	Maximum scanning size	21.6 x 38.1 cm
	Bit depth	30 Bit
	Color scanning	Yes
	Gray scale levels	256
	Scan file format	PDF, JPG, TXT, BMG, TIFF, RTF
	Fax speed	3 sec per page
	Colour faxing	No
	Auto-redialing	Yes
Fax delayed sending	Yes	
Accessories	Driver CDs, Power and Data cables	
Connectivity (Standard)	1 Hi-Speed USB 2.0, 1 Host USB, 10/100/1000 Ethernet network	
Operating System Support	MS XP, Windows 7, 8	




	Warranty	1 year
--	----------	--------



Technical Specifications


Lot 1 - Item No. 4: A4 Scanner		
Item Name	Parameters	Required Specifications
A4 Scanner	Scanner type	Flatbed, ADF Networked Document Flatbed Scanner
	Scan speed (ADF)	Up to 15 ppm / 6ipm (b/w, grey & color)
	Scan resolution Optical/enhanced	Optical: 2400 dpi Hardware: up to 2400 x 2400 dpi, ADF: up to 600 x 600 dpi, Enhanced: up to 19,200 dpi
	ADF capacity Standard	50 sheets
	Bit depth	48-bit
	Maximum document size	A4, A5, custom
	Interface and connectivity	Standard: 1 Ethernet, 1 Hi-speed USB 2.0
	Minimum system requirements	Microsoft Windows XP, 7 and 8
	Multiple file formats	PDF, JPG, TIFF, HTML, RTF, FPX, PNG, PCX, GIF
	Warranty	1 Year




Technical Specifications

Lot 1 - Item No.5: Photocopying Machine


Item Name	Parameters	Required Specifications
Photocopying Machine	Type	Floor Standing
	Device Type	printer / copier / scanner
	Copier Type	digital
	Printing Technology	Laser - monochrome
	ADF facilities	Yes
	Full Duplex	Yes (Standard)
	DADF facilities	Yes
	PC Connection Availability	Yes
	Standard Memory	128 MB
	Max Copying Speed	Up to 20 ppm
	Max Copying Resolution	Up to 600 x 600 dpi
	Max Document Enlargement	400%
	Max Document Reduction	25%
	Max Printing Resolution	Up to 600 x 600 dpi
	Max Printing Speed	Up to 20 ppm
	Scan Element	CCD (charge-coupled device)
Optical Resolution	600 x 600 dpi	




Min Media Size	B5 (6.93 in x 9.83 in)
Max Media Size	A3
Standard Media Capacity	300 sheets
Max Media Capacity	850 sheets
Bypass Feeder Capacity	100 sheets
Output Trays Capacity	250 sheets
Interfaces	USB 2.0
	Network LAN Card
Operating System Support	MS Windows XP, Windows 7, Windows 8, Vista
Photocopy stand	Yes (Floor Standing Type)
Colour Printing/Scanning/Copying	No
Accessories	Tonner cartridge
Warranty	1 year



Technical Specifications			
Lot 1 - Item No.6 Projector			
Item Name	Parameters	Required Specifications	
Projector	Projection System	3LCD, 3-chip technology	
	Projection Method	Front/rear/ceiling mount	
	Resolution	1280 x 800	
	Brightness	2700 lumens	
	Lamp	190 W UHE	
	Keystone correction range	Vertical: $\pm 30^\circ$	
	Contrast ratio	Up to 10,000:1	
	Type	Manual (Optical) Zoom	
	Interfaces		HDMI x 1
			Computer / Component video: D-sub 15 pin x 1
			S-video: Mini DIN x 1
			Composite video: RCA x 1
			USB connector: Type A x 1 (PC-free and other)
			USB connector: Type B x 1 (USB Plug 'n Play)
Speaker	Yes		
Projector Screen (Yes/No)	No		
Supplied accessories	Power cord, wireless remote control, batteries, VGA cable, carrying bag, software CD		
Warranty	1 year		



Technical Specifications		
Item No. 8: Smart UPS RT 3000 VA,230V		
Item Name	Parameters	Required Specifications
Smart UPS RT3000 VA, 230V	Output	
	Output Power Capacity	2.7 kW / 3.0 kVA
	Max Configurable Power	2.7 kW / 3.0 kVA
	Nominal Output Voltage	230V
	Output Connections	(3) IEC Jumpers, (8) IEC 320 C13, (8) (1) IEC 320 C19.
	Input	
	Nominal Input Voltage	230V
	Input Frequency	50/60 Hz +/-3 Hz (auto sensing)
	Input Connections	BS1363A British, IEC320 C20, Schuko CEE7 / EU1- 16P
	Input voltage range for main operations	151 - 302 Adjustable, 160 - 286V
	Input voltages	220 V, 240 V
	Batteries & Runtime	
	Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
	Included Battery Modules	2
	Typical recharge time	3 hour(s)
	Replacement Battery	RBC43
	Expected Battery Life (years)	03-May
	RBC™ Quantity	1
Warranty	1 year	



APC Smart-UPS 3000VA Rack Mount, LCD 3000VA, 230V with SmartConnect Port

SMT3000RMI2UC



Call for More Information

- Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: Documentation CD, Rack mounting hardware, Rack mounting support rails, USB cable


Output	
Output power capacity	2.7kWatts / 3.0kVA
Max Configurable Power (Watts)	2.7kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220 V, 240 V
Topology	Line interactive
Waveform type	Sine wave
Output Connections	(3) IEC Jumpers (8) IEC 320 C13 (1) IEC 320 C19
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	BS1363A British, IEC 320 C20, Schuko CEE 7 / EU1-16P
Cord Length	2meters
Input voltage range for main operations	151 - 302 Adjustable, 160 - 286V
Number of Power Cords	1
Other Input Voltages	220 V, 240 V

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.



Technical Specifications

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	RBC43 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	182 Watts
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, SmartSlot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	320Joules

Physical	
Maximum Height	86MM, 8.6CM
Maximum Width	432MM, 43.2CM
Maximum Depth	683MM, 68.3CM
Rack Height	2U
Net Weight	44.28KG
Shipping weight	51.7KG
Shipping Height	254MM, 25.4CM
Shipping Width	600MM, 60.0CM
Shipping Depth	980MM, 98.0CM
Units per Pallet	8.0

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.




Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	348.0BTU/hr

Conformance	
Approvals	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant


Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.



Technical Specifications


Lot 1- Item No. 9: GPS Hand Set

Item Name	Parameters	Required Specifications	
GPS Hand Set	Physical Dimension	2.4"x6.3"x1.4" (6.1x16x3.6 cm)	
	Weight	230 g with batteries	
	Water rating	IPX 7	
	Battery Type	Rechargeable NiMH pack (included) or 2 AA bateries (not included); NiMH or Lithium	
	Display Type	Transflective, 65 K color TFT	
	Display Size	1.43"x2.15" (3.6 x 5.5cm) ; 2.6"diag (6.6 cm)	
	Display Resolution	160 x 240 pixels	
	Battery Life	16 hours	
	Memory/history	4 GB	
	High-Sensitivity Receiver	Yes	
	Interface	high speed USB and NMEA 0183 compatible	
	GPS should support	GPS/GLONASS with built-in sensors	
	Maps and Memory		
	Basemap	Yes	
	ability to add maps	Yes	
	Accepts data cards	micro SD™ card (not included)	
	Custom POIs (ability to add additional points of interest)	Yes	
	waypoints/favourites/locations	5000	
	Routes	200	
	Tract log	10,000 points, 200 saved tracts	
	Sensors		
	barometric altimeter	Yes	
	Compass	Yes (tilt-compensated 3-axis)	
	Chartplotter Features		
	Area Calculation	Yes	
	Automatic Routine (turn by turn routing on roads)	Yes (with optional mapping for detailed roads)	
	Geocaching-friendly	Yes (paperless)	
	Custom Maps compatible	Yes	
	Hunt/fish calender	Yes	
	Sun and moon information	Yes	
	Camera	Yes (8 mega pixel with autofocus: automatic geotagging)	
	Picture Viewer	Yes	
Connection Compatible (online community where you analyse, categorise and share data)	Yes		




Logitech Group Video Conference System

Item Name	Required TECHNICAL SPECIFICATIONS
Logitech Group Video Conference System	Camera
	Smooth motorized pan, tilt and zoom controlled from remote or console
	Pan +/- 90°
	Tilt +35° / -45
	10x lossless HD zoom
	Field of View
	Diagonal: 90°
	Horizontal: 82.1°
	Vertical: 52.2°
	Full HD 1080p 30fps
	H.264 UVC 1.5 with Scalable Video Coding (SVC)
	Autofocus
	5 camera presets
	Far-end control (PTZ) of ConferenceCam product (with supported services)
	Kensington security slot
	Video mute/unmute LED indicator
	Standard tripod thread
	Remote Control
	Camera, speakerphone, and call control
	5 camera presets
	Docks on speakerphone
	IR 28 foot (8.5 m) range
	CR2032 battery (included)
	SPEAKERPHONE
	Full-duplex performance
	Acoustic echo cancellation
	Noise reduction technology
	Ultra-wideband audio
	Pairs with mobile devices via Bluetooth and NFC
	LCD for caller ID, call duration and other functional response
	LEDs for speakerphone streaming, mute, hold, and Bluetooth
	Tactile buttons for call answer/end, volume and mute, Bluetooth, and camera controls
	5 camera presets for pan, tilt, and zoom settings
	Kensington security slot
	Microphones
	Pickup Range: 19.69 ft (6 m)
	Pickup range with expansion mics: 27.89 ft (8.5 m)
	Four omnidirectional, beamforming microphones
	Frequency response: 100Hz – 11KHz
	Sensitivity: -28 dB +/-3dB
	Distortion: <5% from 200Hz
HUB / CABLES / POWER	
Central Hub connects and powers all components	
Under-table mounting adhesive included	
One cable to camera: 5 m (16.4 ft)	
One cable to speakerphone: 5 m (16.4 ft)	
Extended cables available: 32.81 and 49.22ft (10and 15 m)	
One USB cable for connection to PC/Mac: 7 ft (2 m)	
AC Power adapter with regional plugs	






Power cable: 9.84 ft (3 m)
MOUNT
Dual-purpose bracket works for both wall mounting and tabletop elevation





Technical Specification

Lot 1 Item No. 12 &13

Material Description	Specification	Sample
Infrared Heater IRFC	Nominal data	Wall Mount Infrared Heater 
	Color casing: White Aluminium	
	Color casing, RAL: RAL 9006	
	Ambient working temperature (dry conditions): -20 to 30°C	
	Dimensions and weights	
	Width: 515mm	
	Height: 140mm	
	Depth: 490mm	
	Weight: 3kg	
	Electric heat	
	Current heating: 6.5A	
	Voltage heating: 400V	
	Input power, heater	
	Phase(s): 3	
Maximum element temperature: 2200°C		
Electric Space Heaters	Heating power [kW]: 0/2.5/5.0	
	Ventilator mode: Yes	
	Built-in room thermostat: Yes	
	Power supply [V] / Frequency [Hz]: 3x400V/50Hz	
	Rated current [A]: 7.2	
	Fan diameter [mm]: 230	
	Air flow [m3/h]: 400	
	Product size (LxWxH) [mm]: 305x254x409	
	Net weight [kg]: 6.81 IP: 44	




Technical Specification		
Lot 1 Item No. 14		
Description	Specification	Sample Picture
Industrial Vacuum Cleaner	Function:Wet-Dry Vacuum Cleaner, Container Capacity: 60 -100 Ltr, Input Power: not less than 2200 Watt, Suction Power:not less than 300 mBar, Air Flow:not less than 150 L/s, Noise Level:not more than 70 dB, No. of Motors:1 Motor, Voltage:220-240 V / 50 Hz, Included Components: Mop, Nozzle, Pipe & Extension Tube, Cable Length:not less than 7 m	



Technical Specification for Motorola Hand set (Lot 2, Item No. 1)

Item Name	Required Specification
<p>Motorola MotoTrbo XIR P3688 Digital Portable Handset</p>	<p>Motorola MotoTrbo XIR P3688 Digital Portable Handset with NNTN4497 2250 mAh 7.2 V Battery, Charger Holder, adapter, belt clip, antenna and user manual. Analog/Digital * Voice Communication* Dual Capacity Direct Mode* Digital Mobile Radio (DMR) Standards Complaint * Narrow Banding Complaint * IP54 Rated Battery: Analog 14.5hrs / Digital:18.5 hrs Specification VHF136 to174MHz, 5W, 16Ch / UHF 403-470MHz, 4W Receiver / Transmitter Channel Spacing : 12.5kHz /25kHz2 Analog Sensitivity (12dB SINAD): 0.3uV /0.22uV (Typical) Digital Sensitivity (5%BER): 0.3uV / 0.19uV (Typical) Digital Vocoder Type: AMBE+ 2™ Digital Protocol: ETSITS 102 361-1,-2,-3 Packaging Test: MIL-STD 810D and E Operating Temperature: -30°C / +60° Dust and Water Intrusion: IEC60529 - IP5</p>



Technical Specification

Lot 3 - Item no. 1: Dell Laptop (Standard)


Restricted to Dell Brand Only

Item Name	Parameters	Propose Specifications
Dell Laptop, Standard Type	Storage	512GB M.2 PCIe NVMe Solid State Drive
	Processor	11th Generation Intel® Core™ i5-11320H Processor
	Memory	8GB, 2x4GB, DDR4, 3200MHz
	OS	Windows 11 Home (Recommend 11 Pro)
	Graphics	intel® Iris® Xe Graphics with shared graphics memory
	Screen	15.6-inch FHD
	Battery	4-Cell Battery, 54WHr (Integrated)
	Wireless	Intel® Wi-Fi 6 2x2 (Gig+) and Bluetooth 5.1
	Bag	Bag Pack
	Accessories	Dell External DVD +/- RW Drive: Backlit keyboard
	After Sell Service	Required
	Warranty	1 year

Item no.2: Dell Laptop (Highend)

Restricted to Dell Brand Only

Item Name	Parameters	Propose Specifications
Dell Laptop (high end)	Storage	512GB Solid State Drive
	Processor	11th Generation Intel® Core™ i7-11390H Processor (12MB Cache, up to 5.0GHz with ITBM3.0)
	Memory	16GB, 2x8GB, DDR4, 3200MHz
	OS	Windows 11 Pro
	Screen	15.6" FHD Display
	Battery	Primary 4 Cell 68 W/HR Battery: 90 W AC Adapter
	Graphics	NVIDIA® GeForce® MX450 with 2GB GDDR5 graphics memory
	Wireless	Intel® Wi-Fi 6 2x2 (Gig+) and Bluetooth 5.1
	Bag	Bag Pack
	Docking Station	1 no.
	Accessories	Dell USB Slim DVD +/- RW Drive-DW316, USB-3
	After Sell Service	Required
Warranty	1 year	




Item No. 3: Dell LED Monitor 27"**Restricted to Dell Brand Only**

Item Name	Parameters	Required Specifications
Dell LED Monitor 27"	Display	LED-backlit LCD monitor/ TFT active matrix
	Diagonal size	27"
	Built in Device	USB 3.0 hub
	Panel type	IPS
	Native Resolution	Full HD (1080p) 1920x1080 at 60 Hz
	Pixel Pitch	0.311 mm
	Brightness	300 cd/m. sq.
	Contrast ratio	1000 is to 1
	Connectivity	Interfaces: HDMI, Display port, VGA, USB 3.0 upstream (Type B), 2x USB 2.0 downstream (Type A), 2xUSB 3.0 downstream (Type A)
	Cables included	1x VGA Cable- VGAtO VGA, 1xDisplay port cable-Display port to Display port, 1xsuperspeed USB cable-USB type A to B
	Accessories	Dell Dock with monitor stand, Dell single monitor arm, Dell wireless keyboard and mouse
	After Sell Service	Required
	Warranty	1 year

Item No. 4: Desktop Computer: DELL**Restricted to Dell Brand Only**

Item Name	Parameters	Propose Specifications
Desktop Computer: DELL	Storage	1TB 7200RPM 3.5" SATA HDD
	Processor	10th Gen Intel® Core™ i3-10105 processor
	Memory	8GB, 8Gx1, DDR4, 2666MHz
	OS	Windows 10 Pro (Includes Windows 11 Pro License)
	Graphics	Intel® UHD Graphics 630 with shared graphics memory
		802.11ac 1x1 WiFi and Bluetooth
	Monitor	17" Monitor with LED Backlit
	OD	Optical Disc Dive (R/W)
	Accessories	Key board, Mouse, Driver DVD
	After Sell Service	Required
	Warranty	1 year



Technical specifications for iMac Book

MacBook Pro 13"

Display

Retina Display

- 13.3-inch(Diagonal) LED-backlit display with IPS technology; 2560-by-1600 Native resolution at 227 pixels per inch with support for millions of colors
- Supported scaled resolutions:
 - : 1680 by 1050
 - : 1440 by 900
 - : 1024 by 640
- 500 nits brightness
- Wide color (P3)
- True Tone technology

Chip Apple M1 chip

- 8-core CPU with 4 performance cores and 4 efficiency cores
- 8-core GPU
- 16-core Neural Engine

Battery and Power

- Up to 17 hours wireless web
- Up to 20 hours Apple TC app movie playback
- Built-in 58.2-watt-hour lithium-polymer battery
- 61W USB-C Power Adapter


Memory 8GB

Storage 512GB

: Configurable to : 1TB or 2TB

Charging and Expansion

- Two Thunderbolt / USB 4 ports with support for:
 - : Charging
 - : DisplayPort
 - : Thunderbolt 3 (up to 40Gb/s)
 - : USB 4 (up to 40Gb/s)
 - : USB 3.1 Gen 2 (up to 10Gb/s)



Keyboard and Trackpad

- Backlit Magic Keyboard with:
 - : 65 (U.S.) or 66 (ISO) keys including 4 arrow keys in an inverted-T arrangement
 - : Touch Bar
 - : Touch ID sensor
 - : Ambient light sensor
 - : Force Touch trackpad for precise cursor control and pressure-sensing capabilities; enables Force clicks, accelerators, pressure-sensitive drawing, and Multi-Touch gestures

Wireless

- Wi-Fi
 - : 802.11ax Wi-Fi 6 wireless networking
 - : IEEE 802.11a/b/g/n/ac compatible
- Bluetooth
 - : Bluetooth 5.0 wireless technology

Camera


- 720p FaceTime HD camera

Video Support

- Simultaneously supports full native resolution on the built-in display at millions of colors
 - : One external display with up to 6K resolution at 60Hz
- Thunderbolt 3 digital video output
 - : Native DisplayPort output over USB-C VGA, HDMI, DVI, and Thunderbolt 2 output supported using adapters.

Audio

- : Stereo speakers with high dynamic range
- : Wide stereo sound
- : Support for Dolby Atmos playback
- : Studio-quality three-mic array with high signal-to-noise ratio and directional beamforming
- : 3.5 mm headphone jack



Operating Requirements

- : Line voltage: 100V to 240V AC
- : Frequency: 50Hz to 60Hz
- : Operating temperature: 50° to 95° F (10° to 35° C)
- : Storage temperature: -13° to 113° F (-25° to 45° C)
- : Relative humidity: 0% to 90% noncondensing
- : Operating altitude: tested up to 10,000 feet
- : Maximum storage altitude: 15,000 feet
- : Maximum shipping altitude: 35,000 feet

Size and Weight

- : Height: 0.61 inch (1.56 cm)
- : Width: 11.97 inches (30.41 cm)
- : Depth: 8.36 inches (21.24 cm)
- : Weight: 3.0 pounds (1.4 kg)

Operating System

macOS is the most advanced desktop operating system in the world. macOS Monterey introduces powerful new features to help you connect, share, and create like never before.

