NATURAL RESOURCES DEVELOPMENT CORPORATION LIMITED BJEMO SCIENTIFIC THINNING FOREST ROAD BILL OF QUANTITY

Location: Bjemo, Chabcha, Chukha Length of road: 1000 m

SI no			Descript	ion		Qty	Unit	Rate	Amount	Remarks
1.00	EARTH W	ORKS:	Descript	ion		Qty	Unit	Kate	Amount	Remarks
1.10	a) Clearin		ight-of-way-		etation and					
	a) Clearing jungle including up-rooting of vegetation and felling of trees of girth greater than 300mm & stacking									
	within 50		site.							
	L(m) 1000.00	B(m)	-			10000	m ²			CG0002
	1000.00	10.00				-	111			CG0002
1.20	Evenyetie	n of 400d	Formation C		a in bath sail					
	Excavation of road formation/trace/box cutting in both soil and rock strata using an excavator, including separate									
	stacking of excavated soil, rock, and sandstone materials									
	within 50 meters for reuse. The excavated material shall be transported over a distance of up to 1000 meters,									
	regardless of station markings. All disposed material shall									
		be leveled and neatly dressed. The general formation width								
	shall be 6 meters; however, increased widths shall be adopted at zigs, sharp ridges, and valley sections as									
	instructed by the site supervisor. Cutting width shall be									
	carried out strictly as per the drawings and site instructions.									
						1 000 00	1.6			LLIMPOLIM
	1000 m or 1 km					1,000.00	LS	1		LUMPSUM
2.00	CROSS D	RAINAG	E WORKS:							
2.10										
2.10	Log Culverts Complete construction of log culverts as per the drawings,									
	using suitable road alignment timber with diameter not									
		less than 500 mm. The work includes excavation for foundations, placement and alignment of logs as specified								
	in the drawings including royalty if required, and all									
	associated works required to complete the structure in accordance with design and instructions.									
	4	e with de	sign and mist	uctions.		4.00	Nos			NRDCL
	T									5 52
	Cross Drains Complete construction of cross drains as per the drawings									
	after every 40m interval, using suitable road alignment									
	timber with diameter not less than 500 mm. The work includes excavation for foundations, placement and									
	alignment of logs as specified in the drawings including									
	royalty if required, and all associated works required to									
	complete the structure in accordance with design and instructions.									
	25					25.00	Nos			NRDCL
3 00	ROAD W	UDKE								
	KOAD W	OKKS.								
3.10	Embankment: Construction of embankment by laying dry earth in									
	horizontal layers not exceeding 150mm in depth									
	(compacted), including watering,power rolling,dressing and preparation of site with selected									
	excavated earth within 500 m lead									
	L(m)	W(m)	H(m)	Nos	Volume					
	1000.00		0.3			900.00	m ³			RW0030
	-		1							
3.40	Side Drain									
	Earth work in excavation for side drain over areas using Excavator, exceeding 300mm in depth, 1.5m in width as									
	well as 10 sq.m in area on plan, including dressing,									
	well as 10	levelling and disposal of excavated earth, lead up to 50m								
	levelling a			and lift up to 1.5m in all types of soil and rock both. The rate shall be applicable for both rock and soil portion.						
	levelling a and lift up	to 1.5m	in all types of							
	levelling a and lift up	to 1.5m	in all types of							
	levelling a and lift up rate shall L(m)	to 1.5m be applic	in all types of able for both	rock and soil	volume		_			
	levelling a and lift up rate shall	to 1.5m be applic	in all types of able for both	rock and soil	volume	1000.00	m ³			RW0049
	levelling a and lift up rate shall L(m)	to 1.5m be applic	in all types of able for both	rock and soil	volume	1000.00	m ³			RW0049
	levelling a and lift up rate shall L(m)	to 1.5m be applic	in all types of able for both	rock and soil	volume	1000.00		D TOTAL	:	RW0049
	levelling a and lift up rate shall L(m)	to 1.5m be applic	in all types of able for both	rock and soil	volume	1000.00		D TOTAL	:	RW0049