

| Sl.No | Description | Specification | Brand | Unit | Quantity | Rate(DDP) | Amount (Nu) |
|-------|---|--|-------------------------------------|--------|----------|-----------|-------------|
| 1 | MCCB | TPN(400A, Model Loadline LS | Havells | Nos | 11 | | |
| 2 | MCB | TP 16A | Schneider | Nos | 5 | | |
| 3 | MCB | TP 10A | Schneider | Nos | 5 | | |
| 4 | MCB | TP (Type C, 63 A | Havells/Schneider/Legrand/HP L | Nos | 930 | | |
| 5 | MCB | TPN (Type C, 63 A | Havells/Schneider/Legrand/HP L | Nos | 180 | | |
| 6 | MCB | MCB TP(Type C, 83 A, Model: BCAS3AM80/MUDA0- E for PDU | Havells/Schneider/Legrand/HP L | Nos | 200 | | |
| 7 | LED Drivers | 25 to 36W | Reputed Brand | Nos | 20 | | |
| 8 | Heat shrink | Heat shrink | Reputed Brand | Set | 2 | | |
| 9 | Cable | 16 Sq. mm cable (90m) | mescab/RR cable/ havells | Roll | 1 | | |
| 10 | Cable | 4 core copper cable 2.5sq mm (305m) | mescab/RR cable/ havells | Roll | 1 | | |
| 11 | Cable | 3 core cable 2.5 Sq mm (200m) | mescab/RR cable/ havells | Roll | 1 | | |
| 12 | Cable | 3 C. 2.5 sq mm wire | Havells or equivalent | Roll | 1 | | |
| 13 | Cable | 4 sq mm wire | Havells or equivalent | Roll | 2 | | |
| 14 | CRC | 2-26 Multi Use Electro Cleaner, 500 ml Aerosol Can | CRC | Nos | 100 | | |
| 15 | Silica gel | | YOGYA | Kg | 205 | | |
| 16 | Gasket & O'ring | inner dia 55mm | NU-cork | Set | 190 | | |
| 17 | Transformer Oil | New Mineral insulating oil, low viscosity as per IEC 60296 | APAR, India or SAVITA OIL, India | Barrel | 55 | | |
| 18 | Silicone sealent | Silicone sealent | Reputed Brand | Nos | 35 | | |
| 19 | HT handgloves | HT, 33kV | Reputed Brand | Pair | 4 | | |
| 20 | Handgloves | LV, 415V | Reputed Brand | Pair | 12 | | |
| 21 | Plug-in relay (RMU) | 24VDC, MY4N-GS, 14 PIN | omron | Nos | 20 | | |
| 22 | Current transformer | CTR: 200/1-1A, core: 5P10, 2.5VA, core2: CL-0.5,2.5VA, Resin Cast. Type: protection and metering, | | Nos | 2 | | |
| 23 | Main protection relay | 3 poles over current + earth fault relay with selectable characteristics (CSDPR-V2-200-D-H-N). | CSDPR | Nos | 2 | | |
| 24 | Transformer leak sealent | Transformer leak sealent | Reputed Brand | Nos | 4 | | |
| 25 | Emroy/sand paper | Emroy/sand paper | Reputed Brand | Nos | 20 | | |
| 26 | HT insulation tape | 11-33KV | Jonshon or equivalent | Nos | 25 | | |
| 27 | Lugs | 16 sq.mm lugs, ring type | Reputed brand | Nos | 350 | | |
| 28 | RMU bus coupler end adapter with accessories | EA 36-C32, Make NKT | NKT | set | 4 | | |
| 29 | RMU bus coupler cross adapter with accessories | XA 36-C32 Make NKT | NKT | Set | 4 | | |
| 30 | Spirit | Spirit (Liquid for cleaning purpose) | Reputed Brand | Ltrs. | 10 | | |
| 31 | Air Circuit Breaker | Capacity: 5000A Type: Draw out Model: UW3-50H | U Power OMEGA of L&T | Nos | 3 | | |

| Sl.No | Description | Specification | Brand | Unit | Quantity | Rate(DDP) | Amount (Nu) |
|-------|--|---|---|-------|----------|-----------|-------------|
| 32 | Air Circuit Breaker | 4000Amp 4 pole, EDO ACB with microprocessor based release for Overload, short circuit and EF proection, 50kA fault level with Shunt release of 220-240V AC/DC supply. Type Ref E4.2N 4000 Ekip Dip L.SIG 4P oil filter 90915-20005 Dimension: Product Net Width 551 mm Product Net Height 425 mm Product Net Depth / 383 mm | ABB | Nos | 8 | | |
| 33 | Air Circuit Breaker | Capacity: 4000A Type: Draw out Model: UW2-40S | U Power OMEGA of L&T | Nos | 5 | | |
| 34 | Air Circuit Breaker | Capacity: 2000A, Type: Draw out Model: UW1-20N | U Power OMEGA of L&T | Nos | 8 | | |
| 35 | Air Circuit Breaker | Capacity: 1600A Type: Draw out Model: UW1-16N | U Power OMEGA of L&T | Nos | 11 | | |
| 36 | HV bushing | HV bushing, 52kV/1000A, Porcelain, | CJI Porcelain, India | Nos | 6 | | |
| 37 | LV Bushing | LV Bushing 3.6kV/5000A, Porcelain | CJI Porcelain, India | Nos | 7 | | |
| 38 | Cable termination kit | 33 KV Indoor Type (3cX150 sq mm) RMU end, Boot type | Raychem RPG | Set | 2 | | |
| 39 | Cable termination kit | 33 KV Indoor Type (1cX630 Sq mm) RMU end, Boot type. | Raychem RPG | Set | 2 | | |
| 40 | Cable termination kit | 33KV Outdoor Type (1cX630 sqmm) at A2 end, 3M | Raychem RPG | Set | 4 | | |
| 41 | Cable termination kit | 33 KV Indoor Type (3CX150 sqmm) at Trafo end, 3M | Raychem RPG | Set | 4 | | |
| 42 | Radiator valve | Model 207C-11 | Viat Instruments Pvt Ltd, Kolkota | Nos | 5 | | |
| 43 | Transformer oil filtration hose pipe (10m) | PH253-1" ISO 1436/EN 853 DN25-SAE 100 R1AT-16 MAX WP 88 BAR (1270 PSI) | Polyhose | Nos. | 2 | | |
| 44 | Filtration machine heaters | 3KW | Suitable for 2500LPH,CEE DEE Vaccum Equipment | Nos. | 5 | | |
| 45 | Filtration machine filter candle | | Reputed Brand | Nos. | 5 | | |
| 46 | Vaccum pump oil | | ester oil | Ltrs. | 10 | | |
| 47 | Slogging Spanner | Slogging Spanner Open End (Size 85 mm | Eastman | Nos | 4 | | |
| 48 | Emery/sand paper for metal | | Reputed Brand | Nos | 50 | | |
| 49 | Lugs | 630sqmm Al lugs, ring type | Reputed Brand | Nos | 50 | | |
| 50 | Lugs | 16sqmm Cu lugs, ring type | Reputed Brand | Nos | 150 | | |
| 51 | RMU bus coupler end adapter with accessories | | Reputed Brand | Set | 1 | | |
| 52 | RMU bus coupler cross adapter with accessories | | Reputed Brand | Set | 1 | | |
| 53 | Spirit | Liquid for cleaning purpose | Reputed Brand | Ltrs | 5 | | |

| Sl.No | Description | Specification | Brand | Unit | Quantity | Rate(DDP) | Amount (Nu) |
|-------|--|--|--|--------|----------|-----------|-------------|
| 54 | Water finding paste | AQUADIS water finding paste | KAVERI BAAG Corporation, Mumbai | Bottle | 56 | | |
| 55 | Simulation Kit | Model Matrix simulation kit, Suitable for Protection & Control Unit of L&T ACB | U Power OMEGA of L&T | Nos | 2 | | |
| 56 | Current Transformer | Internal Suitable for Frame#3 draw out type 4pole 5000A ACB | U Power OMEGA of L&T | Nos | 32 | | |
| 57 | Current Transformer | Suitable for Frame#2 draw out type 4pole 4000A ACB | U Power OMEGA of L&T | Nos | 12 | | |
| 58 | Current Transformer | Suitable for frame#1 draw out type 3pole 2000A ACB | U Power OMEGA of L&T | Nos | 23 | | |
| 59 | Current Transformer | Internal Suitable for frame#1 draw out type 3pole 1600A ACB | U Power OMEGA of L&T | Nos | 8 | | |
| 60 | Current Transformer | External Neutral (Suitable for Frame#1 draw out type 2000A ACB | U Power OMEGA of L&T | Nos | 10 | | |
| 61 | CT wire harness | Suitable for Frame#3-4P, Catalog no. CL006920000 | U Power OMEGA of L&T | Nos | 11 | | |
| 62 | CT wire harness | For matrix suitable for Frame#2-4P, Catalog no. CL006900000 | U Power OMEGA of L&T | Nos | 2 | | |
| 63 | CT wire harness | CT wire harness for matrix suitable for Frame#1-3P, Catalog no. CL006870000 | U Power OMEGA of L&T | Nos | 20 | | |
| 64 | Neutral Configurator | Neutral Configurator suitable for draw out type 4 pole 5000A ACB | U Power OMEGA of L&T | Nos | 3 | | |
| 65 | Synthetic Grease | Red Grease MobilithSHC-100 | Mobil | Nos | 21 | | |
| 66 | White Grease | White Grease (33 Medium) | Molykote | Nos | 10 | | |
| 67 | Cable | 34 kV 1C*630 sq mm cable | Havells/KEI/Polycab | Nos | 1 | | |
| 68 | Straight through jointing kit | Type Outdoor cold shrinkable Voltage LV (1.1 kV) Size 1C*630 sq mm XLPE Al. Cable | Raychem/3M/Compaq | Nos | 6 | | |
| 69 | Straight through jointing kit | Type Outdoor Cold shrinkable Voltage MV (33kV) 1C*630 sq mm XLPE Al. Cable | Raychem/3M/Compaq | Nos | 6 | | |
| 70 | Straight through jointing kit | Type Outdoor cold shrinkable Voltage MV (33 kV), Size 3C*150 sq mm XLPE, Al. Cable | Raychem/3M/Compaq | Nos | 3 | | |
| 71 | Self-amalgamating Silicone Rubber Tape | (2.5cm * 3m) (Model Tape 69 | Avinash Techno Solutions Pvt. Ltd, India or equivalent of Scapa Make | Nos | 200 | | |
| 72 | Radiator valve | Model 207C-11, Make Viat Instruments Pvt Ltd, Kolkota) | Viat Instruments Pvt Ltd, Kolkota) | Nos | 5 | | |
| 73 | Oil Temperature indicator | 15A, 240V AC, 2 sets of contact (1-2 alarm, 3-4 trip), capillary length 5 m, Model 1005A | Precimeasure | Nos | 3 | | |
| 74 | Winding Temperature Indicator | 15 A, 240V AC, 2 sets of contact (1-2 alarm, 3-4 trip), capillary length 5 m, Model 1005A | Precimeasure | Nos | 2 | | |
| 75 | Magnetic Oil Gauge | 5 A, 240 V AC, 1 LOLA contact | Sukrut/VIAT | Nos | 2 | | |
| 76 | Current Transformer | Resin cast CT: Ratio 400-200/1-1A Burden: 2.5VA/2.5VA Class: 0.5S/5P10 Freq 50Hz Ins level: 0.72/3kV STC 20kA/3sec Ins class: B | Narayan PowerTech Pvt Ltd, India | Nos | 3 | | |

| Sl.No | Description | Specification | Brand | Unit | Quantity | Rate(DDP) | Amount (Nu) |
|-------|--|--|---|------|----------|-----------|-------------|
| 77 | Stud type terminal connector or connection plate | 63A 4pole) Model: PTPN63 | Pecox India | Nos | 200 | | |
| 78 | Aluminium lugs | Size 95sq mm | Reputed brand | Nos | 64 | | |
| 79 | Cable | LT ABC 4C 95sq mm cable | | Nos | 320 | | |
| 80 | Cleat for cable | Cleat for cable(Size suitable for 1.1kV 1C 630 sq mm XLPE AL Cable, Make reputed brand) | Reputed brand | Nos | 16 | | |
| 81 | Cross Flow Fan | Cross Flow Fan(Model WCFF 80-220, Make WECO, India) | WECO, India | Nos | 1 | | |
| 82 | Rechargeable Battery | Size C, 1.5V (each battery) along with charger | Duracell or EBL | Nos | 8 | | |
| 83 | 2 way splice connectors - long barrel | Suitable for 16sq mm Copper Conductor,Item Catalog code: AFL 6 | Raychem RPG, India | Nos | 300 | | |
| 84 | MX Universal Extension Reel | 6 Amps With 32 Amps Mcb,Fuse 25 Mtr 2 Socket Extension Boards (Black, 25 m) | MX India | Nos | 1 | | |
| 85 | Handing crimping tool | Handing crimping tool (till 16sq mm), Model: SAMRAT 16 | Jainson India | Nos | 2 | | |
| 86 | OC & EF relay | Model: CSPR V5 Horizontal type | C&S Electric India | Nos | 5 | | |
| 87 | TAFU Card / Transformer Fault Annunciation Unit | Model G'LEC | Gogate Electrosystems (Nasik) Pvt. Ltd, India | Nos | 5 | | |
| 88 | Spot Thermal Camera | Model: TG165-X | FLIR | Nos | 1 | | |
| 89 | Spray Pump with motor | YE3-132S-4 5.5KW, 380V, 1460RPM , ac 3 three phase induction electric motor, IP55, F-Insulation, GB/T28575-2020) | Suitable for HC container | Nos | 1 | | |
| 90 | Circulation Pump with motor | Motor Specification: Three-phase asynchronous motor (YE3-160L-2, 18.5 KW, 380V, 2945RPM, IE3-92.4%, IP55 3 phase Induction Motor, F-Insulation, Cos ϕ =0.89, GB/T 28575-2022) Pump specification: light weight vertical multistage centrifugal pump; model-CDMF85-3-2FSWSC, 2900 RPM, 18.5 KW, 2.5 M HEAD. | Suitable for HC container | Nos | 1 | | |
| 91 | Fluid infusion pump with motor | WB70/090D-P, 0.90 KW, 220V, 2900 RPM Single Phase induction motor, (1.2 -7.2 cu.m/h),Q/GDYLO4-2017) | Suitable for HC container | Nos | 1 | | |
| 92 | Under Voltage coil (UV Coil) | 220,240 V; 50 HZ suitable for 5000A incomer Omega ACB | | Nos | 12 | | |
| 93 | Screwdriver | | Taparia | Nos | 67 | | |
| 94 | Heavy duty Screwdriver | | Reputed Brand | Set | 8 | | |
| 95 | Gypsum screw | | Reputed Brand | Box | 48 | | |
| 96 | Wrench | | Reputed Brand | Set | 2 | | |
| 97 | Adjustable wrench | 1-14" | Taparia | Nos | 6 | | |
| 98 | Spanner | (ring & Doe) | Reputed Brand | Set | 4 | | |
| 99 | Combination Pliers | | Reputed Brand | Nos | 22 | | |

| Sl.No | Description | Specification | Brand | Unit | Quantity | Rate(DDP) | Amount (Nu) |
|-------|--|---|--------------------------|------|----------|-----------|-------------|
| 100 | Wire strippers | | Reputed Brand | Nos | 32 | | |
| 101 | Drill bit | | Reputed Brand | set | 18 | | |
| 102 | Grinder blades | | Reputed Brand | Pkt | 44 | | |
| 103 | Gloves | | Reputed Brand | pair | 360 | | |
| 104 | Digital Vernier Caliper | | Reputed Brand | Nos | 1 | | |
| 105 | Marking cothes | | Reputed Brand | mtrs | 1084 | | |
| 106 | Socket with Switch | 16A | Reputed Brand | Nos | 10 | | |
| 107 | Measuring tape | 30m | Reputed Brand | Nos | 4 | | |
| 108 | High Density polyethylene pipe | 20 mm dia. | Reputed Brand | Mtr | 800 | | |
| 109 | Isopropyl | | Reputed Brand | Ltrs | 135 | | |
| 110 | Hand Pallet Lifter | Hand Pallet Lifter(1.5 tonne Manual scissor hand pallet truck with lift height of 800 mm and with fork speed of 520mm, Model GMSHPT 1508 | Godrej India | Nos | 2 | | |
| 111 | Uninterrupted Power Supply | UPS for server room Model; HP3115H, Input: 380VAC/3 phase+N+PE/50Hz/30A/Phase, Output: 220VAC/Single phase+N+PE,50Hz/68A, Capacity: 15KVA//13.5KW | CPSY Power Export | Nos | 1 | | |
| 112 | Steel Rod cutter | | Reputed Brand | Nos | 2 | | |
| 113 | Grass Cutter Machine | (34 CC, 4 Stroke, Weight : 11 kg) | Reputed Brand | Nos | 6 | | |
| 114 | Soldering Machine with Accessories | | HAKKO | Nos | 5 | | |
| 115 | Infrared Thermometer | (-32 deg to 550 deg C) | FLIR | Nos | 2 | | |
| 116 | Infared thermal Camera with extended temperature range | (-20 to 250 degree celcius) | FLIR | Nos | 3 | | |
| 117 | Multimeter | | Fluke | Nos | 6 | | |
| 118 | Cordless drill | 12V | Makita Make | Nos | 18 | | |
| 119 | Cordless drill | 18V | Makita Make | Nos | 9 | | |
| 120 | Heater | 2800 W | Shinil Mkae | Nos | 10 | | |
| 121 | Industrial Vacuum Cleaner | Model : D3080, Power Supply: 220V 50 Hz, Power:3600 W, Negative Pressure: 200mbar, Air Volume:620 cubic meter/hr. | BERSI | Nos | 7 | | |
| 122 | Oil Free Air Compressor | OTS-800X4 | | Nos | 6 | | |
| 123 | Geyser (3L, 2000W, 220-240V, 50Hz) | 3L, 2000W, 220-240V, 50Hz | Jaguer | Nos | 1 | | |
| 124 | Geyser (20L, 2000W, 220-240V, 50Hz) | 20L, 2000W, 220-240V, 50Hz | Jaguer | Nos | 1 | | |
| 125 | Hand Operated Rotary Barrel Pump | Model: RBP/3V: Maximum discharge flow: 38LPM, Capacity: use with 50 to 200 litres oil barrel | Make Groz Net Industries | Nos | 2 | | |
| 126 | Electric Fuel Pump | Model: EDR/55, Make: GROZ Tools, India | GROZ | Nos | 4 | | |
| 127 | Chain Pulley Block | Capacity 1 Ton Lift 3Mtr | KEPRO, India | Nos | 1 | | |
| 128 | Bench Drill Machine | 13mm with Variable Speed Control, | Krost India | Nos | 1 | | |
| 129 | Electric Metal Cut Off/Chop Saw Make: Bosch | 2200W | Bosch | Nos | 1 | | |
| 130 | Clamp on meter | | FLUKE | Nos | 3 | | |

| Sl.No | Description | Specification | Brand | Unit | Quantity | Rate(DDP) | Amount (Nu) |
|-------|------------------------------------|---|---------------|------|----------|-----------|-------------|
| 131 | 10 kV IR Tester | Insulation Tester Type: <ul style="list-style-type: none"> • Digital Megohmmeter • Insulation testing voltage: 500V, 1KV, 2.5 KV, 5 KV, 10KV • Insulation Testing Resistance: up to 20 T-Ohm • Min Functions: Timed IR, PI, DAR, DAD. • Test leads: Jaw opening with minimum length of 10 meters each. • Other features: Analog and digital display, 3 mA short circuit current, rechargeable Li-ion battery, noise reduction, USB output. • Dimension: 315 x 285 x 181mm • Max weight: 5 Kg | Megger | Nos | 1 | | |
| 132 | Transformer oil sampling bottle | | Reputed Brand | Nos | 6 | | |
| 133 | Electrician Tool bag | <ul style="list-style-type: none"> • Dimensions: 430 x 280 X 300mm • Features: Dual side opening storage space large enough for hand tools and power tools. Free-standing rigid structure with a reinforced plastic base to protect from water and dirt. | Reputed Brand | Nos | 5 | | |
| 134 | Step Ladder | Heavy Duty 5+1 Diy Home MX3125 | Reputed Brand | Nos | 48 | | |
| 135 | Trolley | Plastic Foldable Platform Trolley 500kg | SRP brand | Nos | 6 | | |
| 136 | Short Circuit Tool kit | | Reputed Brand | Nos | 1 | | |
| 137 | Solar Panel Cleaning Kit | | Reputed Brand | Nos | 1 | | |
| 138 | Aluminum 5 Ft. Regular Size Ladder | (CODE: L-2)DIMENSION: Platform width = 10inch, Step width = 3inch, Platform height = 60inch, Open width= 50 inch, Weight capacity = 150 kg | MKW brand | Nos | 12 | | |
| 139 | Aircon (2 Ton) | | Reputed Brand | Nos | 1 | | |