










## TECHNICAL SPECIFICATIONS OF LOT 3 (SAFETY EQUIPMENT)




Item No.	Item Description	Unit	Technical Specification	Sample Picture
3(1)	Leather tool pouches (belt type)	NO	<ul style="list-style-type: none"> <li>Belt Width: up to 2" (51 mm)</li> <li>Belt Connection: slotted</li> <li>Overall Size: 6-3/4" (171 mm) x 10" (254 mm)</li> <li>Weight (lbs.): .56 (Leather construction.3 pockets for pliers, folding rule and screwdriver.</li> <li>Has a two-way knife snap.</li> <li>Riveted to assure long life.</li> <li>Pockets for 7" (178 mm), 8" (203 mm) and 9" (229 mm) side-cutting pliers, most screwdrivers, 6' (1.83 m) folding rules, and open end wrenches from 9/16" (14 mm) to 13/16" (21 mm)</li> </ul>	
3(2)	Electrical safety barriers - Cones & Tape	NO	<p>Cone Barricade system consisting belt cassette and double weight ring            Dimension: 12 ½ L x 12 ¼ W x 39 ¾ H inches            Weight: 4kg</p> <p><b>Highly visible, bright yellow hazard protection system</b></p> <ul style="list-style-type: none"> <li>Versatile top design accommodates barricade belt, flashing light and lock-in sign holder.</li> <li>Four-sided shape allows for efficient stacking.</li> <li>Multi-lingual imprinted warning messages provide effective communication with a broad audience.</li> <li>Molded-in slots for easy handling.</li> <li>ANSI and OSHA compliant colour and graphics.</li> </ul>	


3(3)	Insulated rescue stick	NO	<p>Rescue stick for use in dry conditions. Insulating sticks ended by a large hook in order to rescue quickly an electrified victim in case of accident.</p> <table border="1"> <thead> <tr> <th></th><th>Rated Insulation kV</th><th>Ø m m</th><th>Overall length (m)</th><th>Weight (kg)</th></tr> </thead> <tbody> <tr> <td>CS-45 (1)</td><td>45</td><td>28</td><td>1,65</td><td>1,00</td></tr> </tbody> </table> <p>(1) Delivred with wall mounted supports CI - 06 D.</p>		Rated Insulation kV	Ø m m	Overall length (m)	Weight (kg)	CS-45 (1)	45	28	1,65	1,00	
	Rated Insulation kV	Ø m m	Overall length (m)	Weight (kg)										
CS-45 (1)	45	28	1,65	1,00										
3(4)	Welding apron, Leather	NO	<p>Cowhide split leather, heavy duty stitching, tan leather colour. 10.8"x8.7"x1.6"</p>											



3(5)	Auto darkening welding helmet	NO	Fibre Metal 990 Thermo Plastic Welding Helmet -24" viewing area	
3(6)	Safety Helmet white with BPC logo	NO	Safety helmet without face protector, head band Circumference: range from 520mm to 620mm, Class E with BPC Logo on the front, White colour, Type 1: helmet full brim, Full chin band adjustable knob at the back.	
3(7)	LED torch to be used with helmet/cap	NO	<ul style="list-style-type: none"> <li>• Drop test up to 5m</li> <li>• Shatterproof lens</li> <li>• Uses 3x AAA batteries</li> <li>• Waterproof IPx4</li> <li>• Hi-intensity LED, 80 lumens</li> <li>• Spot beam or use the diffuser</li> <li>• Night vision: 2x red LEDs</li> <li>• Pipe inspection: 1x green LED</li> <li>• Comfortable and sturdy 3-way head strap.</li> </ul>	



3(8)	Linemen safety belt	SET	<p>Outer Belt: 45 mm- 50 mm (W) x 1200 mm (L) (Curved),  Inner Belt: 100 mm (W) x 700 mm (L) (Curved) with D-ring x  2pcs &amp; V Square ring x 1pc Lanyard: 3-strand Nylon Rope 14mm-  16mm dia. x 2000 mm -2500 mm (L) with snap hook and 8-Ring,  additional unlocking type retractable lanyard 18 mm (W) x 1300  mm (L) with Snap Hook &amp; Shock Absorber.  Weight: 2 -3kg.  Application for both work Positioning Suspension &amp; Single-Line  Suspension.</p> <p>A <b>sample</b> should be submitted. Bid without sample shall be  considered non-responsive.</p>	
3(9)	Full Body Harness	NO	<p>Full body harness (double hook) with energy /shock absorber,  white colour, Absorber Length- 34cm&amp; Rope Length-120cm,  Polyester , Polyamide, Tensile Strength 2500.00 kilograms, Size:  Universal.</p> <p>A <b>sample</b> should be submitted. Bid without sample shall be  considered non-responsive.</p>	
3(10)	Insulated hand gloves, 36kV	PAIR	<p>Insulated hand gloves 36KV, double laminated.  IEC 60903 or ANSI/ASTM D 120,  Size : 10 Or 11 Inches,  Length : 16 inches or 406mm,  Colour : Solid,  Weight : 800gm.</p>	

3(11)	Insulated hand gloves, low voltage, 1000V	PAIR	<p>Insulated hand gloves low voltage 1000V. Isolated gauntlets, Class : 0 Average thickness : 1.0mm - 1.5mm Weight : 220-320 g</p>	
3(12)	Welding hand gloves	PAIR	<p>Hard-wearing, heat-resisting chrome leather, fully lined and KEVLAR stitched</p>	